

## Mushrooms



Data sheet Nr. 9351- R - 06 Edition: January 2019

## 1. Applications

EUROFLEX® Mushrooms are available in different heights, allowing creation of playing areas for all age groups. The rubber material used is comfortable to sit on, dries quickly when wet, is highly resistant to weathering, does not splinter and is soft and therefore safe. Easy and inexpensive to install.

EUROFLEX® Mushrooms are manufactured by an environment-friendly process and can be recycled as process raw material at the end of their service life.

They can be played on under almost any weather conditions.

2. Material

Rubber granulate: granulated recycled rubber

Binding agent: MDI polyurethane

Mushroom Caps: EPDM rubber granulate Binding agent: MDI polyurethane

3. Characteristics

Colour for Cap: red RAL 3016, green RAL 6021, yellow RAL 1002, blue RAL 5015

Other colour on request

Spots are variable in colour

Colour for Stems: reddish brown

minor colour variations and/or fading possible

4. Dimensions / Tolerances

Dimensions / Weight: 200 x 255 mm (including socket) / approx. 8,0 kg/ unit

 $300 \times 255 \text{ mm}$  (including socket) / approx. 13.0 kg/unit  $400 \times 255 \text{ mm}$  (including socket) / approx. 16.0 kg/unit  $500 \times 255 \text{ mm}$  (including socket) / approx. 20.0 kg/unit

Mushroom Cap: Diameter: 450 mm, Weight: approx. 13 kg

## 5. Test Data

Production facility inspection

EN 1176-1:2017

Migration of certain elements: in accordance with DIN EN 71-3

Fire resistance: Class E (DIN EN 13501-1, 2010)

Chemical resistance: conditionally resistant to acids and bases

## 6. Installation

Use installation bar to screw socket into ground. Continue to screw in until top edge of socket is at ground level. Insert reducing adapter into socket. Insert metal pipe.

Fix in place by tightening screw.

Note the complete installation instruction.

All information without guarantee, subject to change. The Data Sheet is not subject to any change service. Each current and valid from can be recalled at www.kraiburg-relastec.com/euroflex









